

MACHINERY AND EQUIPMENT
WOOD

COVERAGE

Variable depending on use.

TYPICAL USE

- Non-chlorinated, colourless, low viscosity solvent, suitable for **cleaning and removing grease from equipment and machinery**.
- Also perfect for **removing grease and wax from old, worn treatments** on wood to be renovated.
- **Removes bubbles of resin** from untreated wood.
- **Effectively cleans lacquered or painted wood**.
- **Diluent** specific for LIGNUM NATURE oil.

BENEFITS

- **Removes** grease, processing oils, sludge, resins, paraffin, etc.
- **Does not leave halos**.
- **Does not affect** metals, metal alloys or plastics.
- **Highly versatile**.
- **Also ideal** for cleaning **electronic components**.
- **Does not affect** lacquered or painted finishes on wood.
- Cleans the wood without darkening it.
- A **non-chlorinated solvent**.
- **Easy to use**.

APPLICATION METHOD

This product is **ready to use**.

Before applying:

- The **surfaces** to be cleaned must be perfectly **dry**.
- The **tools** must be **clean and dry**.

Tools to be used:

Cloth, rag, medium-soft abrasive pad.

How to apply the product:

- **To clean machinery and tools**, pour the product directly onto the surface or onto a cloth (or rag) and rub until the dirt has been completely removed.
- **To remove old wax/oil treatments and to remove resin from wood**, pour the product onto the surface and wipe with a medium-soft pad until the surface is completely clean.
- **As a diluent for LIGNUM NATURE**, the product can be diluted by up to 50%.

Product evaporation rate:

In a well-ventilated place, at about 20°C, 24 hours may be enough for complete evaporation. In any case, the surface must be dry before proceeding with any subsequent protective treatment.

Tool cleaning:

Once the solvent has evaporated, to remove residues of dirt, the instruments can be washed with soap and water.

HDG Group S.r.l.

Viale Giuseppe Verdi, 3 Loc. SISSA
43018 SISSA TRECASALI (PR) ITALY
Ph. +39 0521 379085
Fax +39 0521 877338
www.hdg.it

PACKAGING

- 1-litre can (box contains 12 pieces)
- 5-litre can (box contains 4 pieces)
- 20-litre can (pallet contains 36 pieces)

Transport packaging consists of **ECO-SUSTAINABLE PALLETS** (with certification of use of wood sourced from PEFC-certified forests).

TECHNICAL DATA

Appearance: liquid
Colour: colourless
Odour: mild, characteristic
Density: 0.752 g/ml
Solubility: soluble in organic solvents; not miscible in water
Melting-freezing point: -10°C
Boiling point: 155°C
Flash point: 73°C

WARNINGS

- Wear gloves and protective clothing when handling the product.

STORAGE

Store the product in its original container, tightly closed, in a cool and ventilated place, away from heat sources. Storage temperature: between +5 °C and +30 °C. Validity: 36 months from production (see batch on the packaging).

LABELLING

Warnings

Danger

Hazard statements

May be fatal if swallowed or enters airways.

Precautionary statements

If medical advice is needed, have product container or label at hand. IF SWALLOWED: immediately call a POISON CENTRE or doctor/physician. DO NOT induce vomiting. Store locked up. Dispose of the product in accordance with local regulations. Repeated exposure may cause skin dryness or cracking. Contains: hydrocarbons, C10-C13, n-alkanes, <2% aromatics.



This information is the result of our broadest scientific and operational experience to obtain the best results on the specific job. However, this information is not binding and does not imply our contractual responsibility, nor an accessory obligation with the contract of sale. It does not exempt the purchaser from their responsibility to personally test our products as to their suitability for their intended use. The information provided on this sheet is based on our current knowledge and, in case of changes due to new technologies and/or developments in the sector, it will be modified. Therefore, the Customer is obliged to verify that this sheet has not become obsolete as a result of being replaced by subsequent versions. If in doubt, contact our Technical Office.